


Description	Value
General information:	
Product name:	ALPHA2 25-60 N 180
Product No:	97993211
EAN number:	5710627540500
Technical:	
Maximum head:	60 dm
TF class:	110
Approvals:	VDE,CE,EAC
Model:	D
Materials:	
Pump housing:	Stainless steel
Pump housing:	EN 1.4308
Pump housing:	ASTM A351-CF8
Impeller:	Composite
Impeller:	PES+30% GF
Installation:	
Range of ambient temperature:	0 .. 40 °C
Maximum operating pressure:	10 bar
Type of connection:	G
Size of connection:	1 1/2 inch
Pressure rating for connection:	PN 10
Port-to-port length:	180 mm
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	0 .. 110 °C
Selected liquid temperature:	60 °C
Density:	983.2 kg/m³
Electrical data:	
Minimum power input - P1:	3 W
Power input P1:	34 W
Mains frequency:	50 / 60 Hz
Rated voltage:	1 x 230 V
Maximum current consumption:	0.04 .. 0.32 A
Enclosure class (IEC 34-5):	X4D
Insulation class (IEC 85):	F
Built-in motor protection:	NONE
Thermal protec:	ELEC
Controls:	
Aut. night:	Y
Others:	
Energy (EEI):	0.17
Terminal box position:	6H
Net weight:	2.14 kg
Gross weight:	2.3 kg
Shipping volume:	0.004 m³
Norwegian NRF no.:	9042056



Pumped liquid = Water
Liquid temperature during operation = 60 °C
Density = 983.2 kg/m³

